Surge Protection
B01WSA0/B0310SA0/B0510SA0

B01WSA0D0013EU-00

Best Surge Protection Capability for Home Device with Maximum Flexibility

CyberPower
Reliability. Quality. Value.

CyberPower's brand new surge protection series offers 1-5 outlets with MOV technology showcasing the outstanding noise-filtering capability for sheltering connected equipment in case of any pulse/surge to occur. The Professional Surge Suppressors are designed for home/office surge protection with featured Child-Safety Shutter, which provides all-around safety level not only for the machine, but also for the users we care. Plus, the compact plugging design also makes a convenient way for carrying and using to ensure the most flexibility. With a life time €25,000 connected equipment guarantee, your equipment has all the protection it needs.



B01WSA0



B0310SA0



B0510SA0

Applications

- Desktop Computer System
- Wireless/VoIP Routers
- Cable/DSL Modems
- Personal Electronics

Series Features

- Professional Grade EMI/RFI Noise Filter
- High Performance Computer Grade Protection
- Electromagnet Device Grade Protection
- Compact Design
- LED Status Indicators

*The series is also available with FR socket









® CyberPower Systems Inc. All Rights Reserved.

Surge Protection
B01WSA0/B0310SA0/B0510SA0

CyberPower®
Reliability. Quality. Value.

Technical Specification

Model Name	B01WSA0	B0310SA0	B0510SA0
General			
Type	Essential		
Input			
Voltage	250Vac		
Switch	Non lighted on/off - reset		
Circuit Breaker	16Amps	10Amps	
Power Cord			
Plug Type	FR/DE Plug		
Plug Style	90 degree		
Cord Length	N/A	3.4'	
Output			
Outlets - Total	1	3	5
Outlet Type	FR/DE Type		
Surge Protection & Filtering			
Surge Suppression	1050J (900J-FR)	350J	700J
Maximum Surge Voltage	6,000 Volts		
Maximum Surge Current	22,500A	7,500A	15,000A
Maximum Surge Current H-N	7,500A		
Maximum Surge Current H-G	7,500A	- -	7,500A
Maximum Surge Current N-G	7,500A	- -	
Clamping Voltage	1200V	L-N 1200V	L-N,L-G 1200V
Response Time	< 1ns		
EMI/RFI Filtration	100 kHz to 100 MHz		
Attenuation	Up to 32dB		
Phone Protection RJ11	1-In, 1-Out(Option)	- -	
Coax Protection RG6 (Gold Plated)	1-In, 1-Out(Option)	- -	
Indicators			
Indicators	Protected		
Physical			
Form Factor	Wall tap	Surge	
Enclosure Construction	PP		
Color	White	Black	
Keyhole Mounting Slots	- -	Yes	
Safety Covers	Yes		
Physical Size			
Dimensions (WxHxD) (mm.)	102 x 70 x 80	215 x 54 x 40	300 x 54 x 40
Weight (g.)	110	250	323
Certifications			
Certifications	CE		
RoHS	RoHS Compliant		
Warranty			
Product Warranty	2 years		
Connected Equipment Guarantee	2 years		
CEG Amount	€25000		

#All specifications are subject to change without notice. ©2014 Cyber Power Systems. All Trademarks are the property of their owners.

RoHS CE

DISTRIBUTED BY:

CyberPower's Manufacturing Facilities are **ISO 9001:2000**, **ISO 14000,** and **QC080000** Approved

® CyberPower Systems Inc. All Rights Reserved.